

# Housewrap

WRAP



REX™ Wrap is a woven and coated polypropylene weather resistant barrier that provides air and moisture protection.

- Tiny micro perforations allow moisture vapor inside the wall cavity to escape, and prevents moisture condensation
- Light weight and easy to install
- Tear resistance reduces jobsite waste
- Meets or exceeds all building codes
- Custom print available at no additional cost (one pallet minimum)

Item	Size	Rolls/Pallet	List/Roll
Rex9100	9 x 100'	50	87.15
Rex9150	9 x 150'	45	130.53
Rex9195*	9 x 195'	40	169.77
Rex10100*	10 x 100'	50	96.84
Rex10150	10 x 150'	45	145.26
Rex10195*	10 x 195'	40	188.85

\*non-stock item

Bluebond Housewrap Tape			
Tape3330	3" x 330'	12 Rolls/Case	19.50/Roll 234.00/Case

While supplies last: receive a free applicator with each full case of Bluebond Housewrap Tape.



Effective 04/01/11

Cancels 10/01/08

# Roofing Underlayment

WRAP



REX™ SynFelt is a high strength woven synthetic roof underlayment that can save you 50% in labor and time expense, compared to 30# felt. Here's why:

- The most slip resistant underlayment in the industry.
- 20 times stronger than felt—won't tear-off or buckle when wet.
- 10X lighter per square and 20X stronger than 30# felt
- 10 squares per roll weighing only 28 lbs
- UV resistant and can be exposed for up to 6 months
- Light gray color reduces heat and provides cooler working surface
- Pre-printed nailing pattern speeds installation

The smartest builders and roofers in America use REX™ SynFelt.

Product Specification		Test Method
Roll Width	48 in.	
Roll Length	250 ft.	
Weight Per Square	2.8 lbs	
Nail Seal Ability	Pass	ASTM D-1970
Water Transmission	Pass	ASTM D-4869
Tensile Strength		ASTM D-828
	MD 96 lbs	
	CD 116 lbs	
Tear Strength		ASTM D-4533
	MD 58 lbs	
	CD 77 lbs	
Pliability	Pass	ASTM D-226
Water Ponding	Pass	ASTM D-779

	REX™ SynFelt	30# Felt Paper
Composite Material	100% Polypropylene	Asphalt
Weight Per Roll	28 lbs	60 lbs
UV-Resistant	YES - Up to 6 months	No
Anti-Slip Surface	YES - Using advanced technology	No
Tear-Resistant	YES - 20x that of 30# Felt	No
Warranty	YES - 25 Years	No
Class A Fire Rated	YES - Offering better roof protection	No
Pre-Printed Nailing Pattern	YES	No
Roll Length	250 lineal feet	72 lineal feet
Roll Width	48 in.	36 in.

Item	Size	List/Roll
Felt4250	4' x 250' (10 squares)	246.00



Effective 04/01/11

Cancels 10/01/08